

Product datasheet

Specifications



APC Smart-UPS On-Line, 5kVA/
5kW, Rack/Tower, 230V, 2x IEC
C13+1x IEC C19+Hard wire 3-wire
(H+N+E) outlets, Network Card, W/
O rail kit

SRTG5KXLI




Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	5000 W
Rated Power In Va	5000 VA
Output Connection Type	2 IEC 60320 C13 1 IEC 60320 C19
Output Connector Type	Hard wire 3-wire (1P + N + E) 1
Number Of Rack Unit	4U
Provided Equipment	1 x USB cable 1 x rack mounting brackets 1 x stabilization/wall mounting feet 1 x installation manual 1 x C13-C14 power cord

Batteries & Runtime

Run Time	View Runtime Graph 
Efficiency	View Efficiency Graph 
Battery Type	Lead-acid battery
Number Of Battery Filled Slots	2
Number Of Battery Free Slots	0
Battery Recharge Time	4 h
Number Of Battery Replacement Quantity	1
Battery Voltage	+/- 96 V
Battery Charger Power	239 W rated
Battery Life	3...5 year(s)
Replacement Battery	APCRBC170 

Extended Runtime	1
------------------	---

General

Ups Type	Double conversion online
----------	--------------------------

Number Of Power Module Free Slots	0
-----------------------------------	---

Number Of Power Module Filled Slots	0
-------------------------------------	---

Redundant	No
-----------	----

Physical

Colour	Black (RAL 9005)
--------	------------------

Height	17.5 cm
--------	---------

Width	44 cm
-------	-------

Depth	62 cm
-------	-------

Net Weight	55.9 kg
------------	---------

Mounting Preference	Lower
---------------------	-------

Mounting Mode	Rack-mounted with kit
---------------	-----------------------

Two Post Mountable	0
--------------------	---

Usb Compatible	Yes
----------------	-----

Mounting Position	Horizontal
-------------------	------------

Input

Network Frequency	40...70 Hz auto-sensing
-------------------	-------------------------

Number Of Input Connectors	1 hard wire 3-wire (1P + N + E)
----------------------------	---------------------------------

Input Voltage Limits	160...285 V full load
----------------------	-----------------------

Maximum Input Current	30 A
-----------------------	------

Switching Current Capacity	40 A
----------------------------	------

Output

Maximum Configurable Power In Va	5000 VA
----------------------------------	---------

Maximum Configurable Power In W	5000 W
---------------------------------	--------

Output Frequency	50/60 Hz +/- 4 Hz sync to mains
------------------	---------------------------------

Wave Type	Sine wave
-----------	-----------

Efficiency	93.5 %
------------	--------

Harmonic Distortion	Less than 2 %
---------------------	---------------

Crest Factor	3 : 1
--------------	-------

Bypass Type	Internal bypass (automatic and manual)
-------------	--

Additional Information	Configurable for 220 : 230 or 240 nominal output voltage
------------------------	--

Conformance

Product Certifications	CE UKCA TISI
------------------------	--------------------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
------------------	--

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...15000 m
Acoustic Level	55 dBA
Heat Dissipation	1108.95 Btu/h
Ip Degree Of Protection	IP20

Communications & Management

Preinstalled Device	Network management card 3 with environmental monitoring
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off	Yes

Surge Protection and Filtering

Surge Energy Rate	600 J
--------------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	27.5 cm
Package 1 Width	79 cm
Package 1 Length	59 cm
Package 1 Weight	61.8 kg

Contractual warranty


Warranty	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performances. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)

Well-being performance

 Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
