



### Overview

Model Name	APC Smart-UPS 750VA LCD 230V with SmartConnect
Includes	CD with software
Standard Lead Time	Usually Ships within 2 Weeks
Product Distribution	Albania

### Output

Output Power Capacity	500 Watts / 750 VA
Max Configurable Power (Watts)	500 Watts / 750 VA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240V
Other Output Voltages	Line Interactive
Waveform Type	Sine wave
Output Connections	(2) IEC Jumpers (Battery Backup)

### Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Cord Length	1,83 meters
Input voltage range for main operations	160 - 280 V
Input voltage adjustable range for mains operation	151 - 302V
Other Input Voltages	220

### Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3 hour(s)
Replacement Battery	RBC48

RBC Quantity	1
--------------	---

## Communications & Management

Interface Port(s)	SmartSlot
Available SmartSlot™ Interface Quantity	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Optional

## Surge Protection and Filtering

Surge energy rating	540 Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Physical

Maximum Height	158.0 mm
Maximum Width	138.0 mm
Maximum Depth	359.0 mm
Net Weight	13.18 kg
Shipping Weight	14.23 kg
Shipping Height	301.0 mm
Shipping Width	278.0 mm
Shipping Depth	499.0 mm
Color	Black
Units per Pallet	24.0

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	40.000 dB
Online Thermal Dissipation	90.000 BTU/hr

## Conformance

Approvals	CE
Standard warranty	3 years repair or replace (excluding battery) and 2 year for battery

## Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs