# logitech®



# DATA SHEET

# RALLY ACCESSORIES

Logitech Rally family includes a full suite of accessories to accommodate a wide range of room sizes and configurations. Multiple mounting, mic, and speaker options provide the convenience of conferencing solutions at scale.

# **ACCESSORIES TO SUIT EVERY MEETING SPACE**

Logitech Rally Bar Mini, Rally Bar, and Rally offer premier video collaboration solutions for all room shapes and sizes. Simple, versatile, and meticulously designed for scale, the Rally all-in-one video bars and the modular Rally system offer clutter-free cable management, multiple mounting, mic and speaker options, and the flexibility to deploy in USB or appliance mode. Add Rally accessories to create the best meeting space for your needs.

# **ACCESSORIES FOR RALLY FAMILY**



#### **RALLY MIC POD**

Expand audio coverage with modular, beamforming microphones with RightSound $^{\text{TM}}$  technology for clear, natural, conversational sound.

Auto levels voices, suppresses background noise, and dampens vibration for clear audio

Convenient mute control and indicator light

Available in graphite or white

#### **General Specifications**

Frequency response: 90Hz – 16kHz

Sensitivity: >-27dB +/-1dB @ 1Pa

Microphone data rate output: 48 kHz

Pickup range: 15 ft / 4.5m

Beamforming elements: Four omnidirectional microphones forming eight acoustic beams

Audio processing: AEC (Acoustic Echo Cancellation), VAD (Voice Activity Detector)

Noise suppression: Al filter

Mute Control:

Touch-sensitive mute control with color-coded LED indicator

#### Interfaces & Cables

Output: 9.6 ft (2.95m) 12-pin captive cable

Input: 12-pin interface to daisychain Mic Pods or connect to Rally Mic Pod Hub

## Certifications

Rally Mic Pod, White: Plenum Rated, Eca/ IEC 60332-1-2 Compliant

Rally Mic Pod, Graphite: N/A

# System Requirements

Rally: Up to 7 Mic Pods (one Rally Mic Pod included with system)

Rally Plus: Up to 7 Mic Pods (two Rally Mic Pods included with system)

Rally Bar: Up to 3 Mic Pods (complements the built-in microphone array)

Rally Bar Mini: Up to 2 Mic Pods (complements the built-in microphone array)

Note: Rally Mic Pods are not compatible with the standalone USB Rally Camera.

#### **Product Dimensions**

Height: 0.83 in (21 mm) Width: 4.01 in (102 mm) Depth: 4.01 in (102 mm)

# **Package Contents**

Rally Mic Pod
Documentation

#### **Part Numbers**

Graphite: 989-000430 White: 952-000038





#### **RALLY MIC POD MOUNT**

Rally Mic Pod Mount secures connections and hides cables to give meeting rooms a professional look.

Hide cables and anchor mics on the table or ceiling

Adjusts to fit most tables

Available in graphite or white

#### **General Specifications**

Compatible Devices: Rally Mic Pod Table Thickness: 0.75 - 2.0in (20 - 50mm)

Grommet Hole Diameter: 1.0 - 2.5in (25 - 65mm)

#### **Product Dimensions**

Height: 3.54 in / 90mm Width: 5.75 in / 146mm Depth: 5.75 in / 146mm

#### **Package Contents**

Mic Pod Mount Cup

Threaded Rod

Nut

Cable Spool

Mounting Plate

Screws

Documentation

#### **Part Numbers**

Graphite: 952-000002 White: 952-000020

# **ACCESSORIES FOR RALLY FAMILY**







#### MIC POD PENDANT MOUNT

Ceiling pendant mount for Rally Mic Pod microphones.

Mic Pod Pendant Mount allows you to hang Rally Mic Pods in rooms that have tall ceilings and tables that can't have mics attached or that have unique setups. Hanging mics from the ceiling helps ensure everyone can be heard equally, even in your largest spaces.

#### **Dimensions: Ceiling Mount**

Height: 80 mm Width: 82 mm

#### **Dimensions: Mic Holder**

Height: 56 mm Width: 145 mm

## **Package Contents**

Ceiling Mount

Mic Holder

Mounting Hardware

Quick Start Guide

#### Color

White

#### **Part Number**

952-000123

# Warranty

2-Year Limited Hardware Warranty

#### **RALLY MIC POD HUB**

Connect up to three Rally Mic Pods for hub-and-spoke layouts for flexible placement and efficient cable routing.

Customize for most any meeting table configuration

Reduces cross-table cabling

Connects both mic pods and additional hubs

#### **General Specifications**

Three 12-pin connections for any combination of Rally Mic Pods or additional Rally Mic Pod Hubs

Under-table mounting hardware

Captive 9.6ft (2.95m) 12-pin cable

# **System Requirements**

Rally or Rally Plus

Rally Bar or Rally Bar Mini

configured with external Rally Mic Pods

#### **Product Dimensions**

Height: 0.63in / 16mm

Width: 4.01in / 102mm

Depth: 4.01in / 102mm

# Package Contents

 $\operatorname{\mathsf{Mic}}\operatorname{\mathsf{Pod}}\operatorname{\mathsf{Hub}}$ 

Mounting Hardware

Documentation

#### Part Number

# **ACCESSORIES FOR RALLY FAMILY**



#### **RALLY MIC POD EXTENSION CABLE**

Add 10 meters of additional reach to the cabling of Rally Mic Pod or Rally Mic Pod Hub for larger spaces.

Plenum-rated and Eca certified for commercial installations

Fits within standard 19mm conduit

Connect up to two cables for a total extension of 20 meters

#### **General Specifications**

Extension cable with built-in cable retention clips

Fits standard 19mm conduit

#### Certifications

Plenum Rated, Eca/IEC 60332-1-2 Compliant

#### **System Requirements**

Rally Bar (supports up to 2 cables)

Rally Bar Mini (supports up to 2 cables)

Rally (supports 1 cable)

Rally Plus (supports 1 cable)

#### **Product Dimensions**

Cable Length: 32.80 ft (10 m) Cable Thickness: 0.16in (4.2 mm)

#### **Package Contents**

Rally Mic Pod Extension Cable

Documentation

#### **Part Number**

952-000047



#### **RALLY MIC POD CAT COUPLER**

To extend the length of the connection for Rally Mic Pods and Mic Pod Hubs to a custom length, connect the Rally Mic Pod CAT Coupler to a standard CAT cable.

#### **General Specifications**

Compatible devices: Rally Mic Pods that are connected to Rally Bar, Rally Bar Mini, Rally, and Rally Plus.

#### **Product Dimensions - Reversible Interface**

Height: 15mm Width: 22mm

Depth: 58mm

Cable length 215mm

# **Package Contents**

Coupler x 2

Patch cable

User documentation

#### **Part Number**

# **ACCESSORIES FOR RALLY VIDEO BARS**



#### TV MOUNT FOR VIDEO BARS

Float Rally Bar Mini or Rally Bar above or below a TV or monitor for a sleek installation and minimal footprint.

Flexible and flush mounting depths and thoughtful cable routing Fits most displays with versatile swing-arm design

Optimizes viewing angle for above-display installations with 10° tilt down adapter

# **General Specifications**

Swing-arm design

Mount compatible devices above or below the display

Adjustable depth up to 50mm

Adjustable horizontal level +/- 1°

10° video bar tilt down adapter for above-display angle optimization

# Compatibility

Wall or cart-mounted displays up to 98in (247.92 cm) with VESA mounting points

#### **System Requirements**

Rally Bar

Rally Bar Mini

Rally Camera

# **Product Dimensions**

Swing-arm length (max.): 2.95 ft / 900mm

#### **Package Contents**

VESA-compatible TV Mount Mounting Plate for Rally Bar Mounting Plate for Rally Bar Mini

Fasteners and mounting hardware

#### **Part Number**

952-000041



#### WALL MOUNT FOR VIDEO BARS

Mount Rally Bar Mini or Rally Bar on the wall for a finished appearance and minimal footprint.

Works with video bar's built-in cable retention cover for a secure connection

VESA mounting pattern compatible with mobile carts

Optimizes viewing angle for elevated placement with 10° tilt down adapter

#### **General Specifications**

Mounts compatible devices to a wall or mobile cart

Adjustable horizontal level +/- 1°

10° video bar tilt down adapter for high-position angle correction

## Compatibility

Also compatible with mobile carts with a standard VESA mounting pattern

# **System Requirements**

Rally Bar

Rally Bar Mini

#### **Product Dimensions**

Height: 3.94 in / 100mm Width: 9.29 in / 236mm Depth: 3.31 in / 84mm

#### **Package Contents**

Wall Mount

Tilt Down Adapter

Screws

Documentation

# Part Number

# **ACCESSORIES FOR RALLY SYSTEM (RALLY AND RALLY PLUS)**





#### **RALLY MOUNTING KIT**

For the modular Rally system, includes mounts for the camera, speakers, and hubs for a neat appearance and secure, unobtrusive cabling.

Sturdy camera mount inverts 180° to support near-ceiling installation

Float speakers on the wall with two low profile brackets Includes ventilated mounts and cable retention brackets for Table and Display hubs

Available in graphite or white

#### **General Specifications**

Mounts for the Rally system's camera, speakers, and hubs Invertible camera bracket for near-ceiling installation Low-profile speaker brackets for a floating appearance Ventilated hub mounts with cable retainers

#### Compatibility

Logitech Rally or Logitech Rally Plus

Note: Rally Mounting Kit is designed for Logitech Rally systems only. Rally Mic Pod Mount available separately.

#### **Package Contents**

Camera Bracket (1)

Speaker Brackets (2)

Table Hub Mount

Display Hub Mount

Hub Mount Cable Retainers (2)

Fasteners

Documentation

#### Part Number

939-001644

#### **RALLY SPEAKER**

Add a second speaker to Rally systems originally configured with a single speaker.

Broadens the soundstage for room-filling sound at comfortable volume levels

Receives both signal and power from the Rally Display Hub Pleasing symmetrical appearance

#### **General Specifications**

High-performance 76 mm driver with rare-earth magnet

Patent-pending suspension system eliminates vibrationinduced camera shake and audio interference

Mini XLR cable (9.6 ft / 2.95m) connects to Rally Display Hub for both signal and power

Compatible with customersupplied Mini XLR extension cables up to 9.8 ft (3m)

Speaker volume: 95 dB SPL @1 W, 100 dB SPL @7.5 W, both +/-2 dB at ½ meter

Distortion: 200 Hz-300 Hz < 2.5%, 300 Hz-10 kHz < 1%@7.5 W

Speaker sampling rate: 48 kHz

#### System Requirements

Logitech Rally system with one speaker

Maximum speakers per system: 2

Note: Not compatible with Rally Bar, Rally Bar Mini, or the standalone USB Rally Camera.

# **Product Dimensions**

Height: 4.05 in / 103mm Width: 17.67 in / 449mm Depth: 3.15 in / 80mm

#### **Package Contents**

Rally Speaker with captive 9.6 ft (2.95m) Mini XLR cable

Documentation

#### **Part Number**

# **ACCESSORY COMPATIBILITY**









Product Name	RALLY BAR MINI	RALLY BAR	RALLY	RALLY PLUS	RALLY CAMERA
Rally Mic Pod	Up to 2*	Up to 3*	Up to 7 (1 included)	Up to 7 (2 included)	
Rally Mic Pod Mount	⊘*	<b>⊘</b> *	<b>⊘</b>	<b>©</b>	
Mic Pod Pendant Mount	⊗*	⊘*	<b>⊘</b>	<b>②</b>	
Rally Mic Pod Hub	<b>*</b>	<b>*</b>	<b>②</b>	<b>②</b>	
Rally Mic Pod Extension Cable	⊘*	<b>⊘</b> *	<b>©</b>	<b>©</b>	
Rally Mounting Kit			<b>Ø</b>	<b>Ø</b>	Wall mount included
TV Mount for Video Bars	$\odot$	$\odot$			<b>⊘</b>
Wall Mount for Video Bars	$\odot$	$\odot$			Wall mount included
Swytch	$\odot$	$\odot$	$\odot$	$\odot$	$\odot$

<sup>\*</sup>When the built-in microphone array is extended with external Rally Mic Pods

#### **WARRANTY**

2-year limited hardware on all Rally Accessories

#### **DEVICE MANAGEMENT**

Logitech Sync supports device management for Rally Mic Pod, Rally Mic Pod Hub, and Rally Speaker accessories

#### PRODUCT INFORMATION

Rally Mic Pod:

www.logitech.com/mic-pod-for-rally

Rally Mic Pod Extension Cable:

www.logitech.com/rally-mic-ext-cable

Rally Mounting Kit:

www.logitech.com/rally-mounting-kit

Mic Pod Mount:

www.logitech.com/mic-pod-mount

TV Mount For Video Bars:

www.logitech.com/tv-mount-video-bar

Rally Speaker:

www.logitech.com/rally-speaker

Rally Mic Pod Hub:

www.logitech.com/hub-for-rally-mic-pod

Wall Mount For Video Bars:

www.logitech.com/wall-mount-video-bars

Swytch:

www.logitech.com/swytch

www.logitech.com/vc

Americas

7700 Gateway Blvd Newark, CA 94560 USA **Logitech Europe S.A.** EPFL - Quartier de

EPFL - Quartier de l'Innovation Daniel Borel Innovation Center CH - 1015 Lausanne Logitech Asia Pacific Ltd.

Tel: 852-2821-5900 Fax: 852-2520-2230 © 2022 Logitech. Logitech, the Logitech logo and other Logitech marks are owned by Logitech and may be registered. All other trademarks are the properties of their respective owners. Logitech assumes no responsibility for any errors that may appear in this publication. Product, pricing and feature information contained herein is subject to change without notice.