


# **OVERVIEW**



1. Smart card reader *	6. Thunderbolt 4
2. USB 3.2 Gen 1	7. HDMI
3. Kensington Nano Security Slot	8. USB 3.2 Gen 1 (Always On)
4. Ethernet (RJ-45)	9. Headphone / microphone combo jack (3.5mm)
5. Thunderbolt 4	10. Nano-SIM card slot *

#### Notes

• Items with \* are only available on selected models



# **PERFORMANCE**

# **Processor**

### **Processor Family**

13th Generation Intel® U or P Series Core i5 / i7 Processor

### Processor\*\*[1]

Processor Cores		Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Core i5-1335U 10 (2 P-core + 8 E-core)		12	P-core 1.3GHz / E-core 0.9GHz	P-core 4.6GHz / E-core 3.4GHz	12MB	Intel® Iris® Xe Graphics
Core i5-1340P	12 (4 P-core + 8 E-core)	16	P-core 1.9GHz / E-core 1.4GHz P-core 4.6GHz / E-core 3.4GHz		12MB	Intel® Iris® Xe Graphics
Core i5-1345U	10 (2 P-core + 8 E-core)	12	P-core 1.6GHz / E-core 1.2GHz	P-core 4.7GHz / E-core 3.5GHz	12MB	Intel® Iris® Xe Graphics
Core i5-1350P	12 (4 P-core + 8 E-core)	16	P-core 1.9GHz / E-core 1.4GHz	P-core 4.7GHz / E-core 3.5GHz	12MB	Intel® Iris® Xe Graphics
Core i7-1355U 10 (2 P-core + 8 E-core)		12	P-core 1.7GHz / E-core 1.2GHz	P-core 5.0GHz / E-core 3.7GHz	12MB	Intel® Iris® Xe Graphics
Core i7-1360P	12 (4 P-core + 8 E-core)	16	P-core 2.2GHz / E-core 1.6GHz	P-core 5.0GHz / E-core 3.7GHz	18MB	Intel® Iris® Xe Graphics
Core i7-1365U	10 (2 P-core + 8 E-core)	12	P-core 1.8GHz / E-core 1.3GHz	P-core 5.2GHz / E-core 3.9GHz	12MB	Intel® Iris® Xe Graphics
Core i7-1370P 14 (6 P-core + 8 E-core)		20	P-core 1.9GHz / E-core 1.4GHz	P-core 5.2GHz / E-core 3.9GHz	24MB	Intel® Iris® Xe Graphics

# Notes:

[1] Intel® Iris® Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel® Iris® Xe Graphics will function as Intel® UHD Graphics.

Intel® P series processors are for special bid only.

# **Operating System**

# Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Windows® 11 DG Windows® 10 Pro 64
- Windows® 10 IoT Enterprise LTSC 2021[1]
- Ubuntu Linux<sup>[2]</sup>
- Linux<sup>[3]</sup>
- · No preload operating system

### Notes:

[1] Windows® 10 IoT Enterprise LTSC 2021 is for special bid only.

[2], [3] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

# **Graphics**

# Graphics\*\*

Graphics	Туре	Memory	Key Features	
Intel® Iris® Xe Graphics[1]	Integrated	Shared	DirectX® 12.1	
NVIDIA® GeForce MX550[2]	Discrete	4GB GDDR6	DirectX® 12	

#### Notes:

[1] Intel® Iris® Xe Graphics capability requires system to be configured with dual-channel memory. On the system with



single-channel memory, Intel® Iris® Xe Graphics will function as Intel® UHD Graphics.

[2] Discrete graphics is available only with Intel® P series processors.

# **Monitor Support**

# Monitor Support[1]

Supports up to 4 independent displays (native display and 3 external monitors via Thunderbolt™ and HDMI®)

- HDMI® supports up to 4K@60Hz
- Thunderbolt<sup>™</sup> supports up to 5K@60Hz

#### Notes:

[1] Refresh rates >60hz also supported, however max resolution will be limited.

# Chipset

# Chipset

Intel® SoC (System on Chip) platform

# **Memory**

### Max Memory[1]

- Models with DDR4 memory: up to 40GB (8GB soldered + 32GB SO-DIMM) DDR4-3200
- Models with DDR5 memory: up to 32GB (16GB soldered + 16GB SO-DIMM) DDR5-5200
- Models with 16GB LPDDR5x: 16GB soldered memory, not upgradable
- Models with 32GB LPDDR5x: 32GB soldered memory, not upgradable

### Memory Slots\*\*

- Models with DDR4 memory: one memory soldered to systemboard, one DDR4 SO-DIMM slot, dual-channel capable
- Models with DDR5 memory: one memory soldered to systemboard, one DDR5 SO-DIMM slot, dual-channel capable
- · Models with LPDDR5x memory: memory soldered to systemboard, no slots, dual-channel

### Memory Type\*\*

- DDR4-3200 (models with integrated graphics)
- DDR5-5200 (models with integrated graphics)<sup>[2]</sup>
- LPDDR5x-4800 (models with discrete graphics)[3]

### Notes:

- [1] The max memory is based on the test results with current Lenovo® memory offerings.
- [2] Installed memory is actually DDR5-5600 but run as DDR5-5200 due to platform limitation.
- [3] Installed memory is actually LPDDR5x-7500 but run as LPDDR5x-4800 due to platform limitation.

# Storage

## Storage Support[1]

One drive, up to 2TB M.2 2280 SSD

### **Storage Slot**

One M.2 2280 PCIe® 4.0 x4 slot

# Storage Type\*\*

Disk Type	Interface	Offering	Security
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB / 512GB / 1TB	Opal 2.0
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4 Performance	512GB / 1TB / 2TB	Opal 2.0

#### Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

# **Removable Storage**

# Card Reader

No card reader

# Multi-Media

# **Audio Chip**



High Definition (HD) Audio, Realtek® ALC3287 codec

#### **Speakers**

Stereo speakers, 2W x2, Dolby Audio™

### Microphone

- Dual-microphone array, 360° far-field, Dolby Voice®
- No microphone<sup>[1]</sup>

#### Camera\*\*

- 5.0MP + IR discrete, with privacy shutter, fixed focus
- FHD 1080p + IR hybrid, with privacy shutter, fixed focus
- HD 720p, with privacy shutter, fixed focus
- No camera<sup>[2]</sup>

#### Notes:

[1] No microphone is for special bid only.

[2] No camera is for special bid only.

# **Battery**

### Battery\*\*[1]

- 39.3Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter
- 52.5Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

### Battery Life[2]

Configuration 1 (max battery life) MobileMark® 25: up to 9.5 hr @250nits JEITA 2.0: up to 21.7 hr @150nits Local video playback: up to 17.5 hr @150nits

Alternate configuration 2 MobileMark® 25: up to 9.2 hr @250nits JEITA 2.0: up to 20.3 hr @150nits

Local video playback: up to 17.0 hr @150nits

Alternate configuration 3 MobileMark® 25: up to 7.2 hr @250nits JEITA 2.0: up to 12.9 hr @150nits Local video playback: up to 11.7 hr @150nits

### Notes:

[1] Rapid charge is only guaranteed when the computer is turned off or in standby mode or in hibernation mode. When the computer is powered on, the Charge Time will vary depending on system power consumption and AC adapter power.

[2] Configuration 1 (max battery life): WUXGA low power (non-touch), Intel® i5-1335U, 16GB soldered DDR5, Win 11, 52.5Wh battery, best power efficiency power mode

Alternate configuration 2: WUXGA low power (non-touch), Intel® i5-1340P, 16GB soldered DDR5, Win 11, 52.5Wh battery, best power efficiency power mode

Alternate configuration 3: WUXGA (touch), Intel® i5-1350P, 16GB soldered DDR5, Win 11, 52.5Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using MobileMark® 25, JEITA 2.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to Microsoft® link for more information about the Windows® Performance power slider.

### **Power Adapter**

# Power Adapter\*\*[1]

- 45W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C<sup>®</sup> (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz



- 65W USB-C® slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter<sup>[2]</sup>

Notes:

- [1] AC adapter offerings depend on the country.
- [2] No power adapter is for special bid only.

# **DESIGN**

# **Display**

# Display\*\*

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle (L/R/U/D)	Key Features
14"	WUXGA (1920x1200)	None	IPS <sup>[1]</sup>	300nits	Anti-glare	16:10	700:1	45% NTSC	85° / 85° / 85° / 85°	-
14"	WUXGA (1920x1200)	Multi- touch	IPS <sup>[2]</sup>	300nits	Anti-glare	16:10	700:1	45% NTSC	85° / 85° / 85° / 85°	-
14"	WUXGA (1920x1200)	None	IPS <sup>[3]</sup>	400nits	Anti-glare	16:10	800:1	100% sRGB	85° / 85° / 85° / 85°	Low power, Eyesafe® Certified 2.0
14"	WUXGA (1920x1200)	Multi- touch	IPS <sup>[4]</sup>	500nits	Anti-glare	16:10	1000:1	100% sRGB	85° / 85° / 85° / 85°	ThinkPad® Privacy Guard
14"	2.2K (2240x1400)	None	IPS <sup>[5]</sup>	300nits	Anti-glare	16:10	1500:1	100% sRGB	85° / 85° / 85° / 85°	Eyesafe® Certified 2.0
14"	2.8K (2880x1800)	None	OLED	400nits	Anti-glare, anti- reflection, anti-smudge	16:10	100,000:1	100% DCI-P3	85° / 85° / 85° / 85°	DisplayHDR™ True Black 500, Dolby Vision®, Eyesafe® Certified 2.0

### **Touchscreen**

- On-cell multi-touch, supports 10-point touch
- Non-touch

Notes:

[1], [2], [3], [4], [5] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

# **Input Device**

Pen

No support

# Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

### **Keyboard Backlight**

- · LED backlight
- Non-backlight

#### UltraNav™

TrackPoint® pointing device and glass-like Mylar® surface multi-touch 3-button Trackpad, 61 x 115 mm (2.40 x 4.53 inches)

# Mechanical

### Dimensions (WxDxH)[1]

317.7 x 226.9 x 17.9 mm (12.51 x 8.93 x 0.70 inches)

# Weight<sup>[2]</sup>

Models	Weight
Models with thunder black cover, integrated graphics and 39.3Wh battery	Starting at 1.32 kg (2.92 lbs)



Models with storm grey cover and 39.3Wh battery	Starting at 1.36 kg (3.0 lbs)
Models with thunder black cover, integrated graphics and 52.5Wh battery	Starting at 1.37 kg (3.01 lbs)
Models with thunder black cover, discrete graphics and 39.3Wh battery	Starting at 1.38 kg (3.05 lbs)
Models with storm grey cover and 52.5Wh battery	Starting at 1.40 kg (3.09 lbs)
Models with thunder black cover, discrete graphics and 52.5Wh battery	Starting at 1.42 kg (3.14 lbs)

#### Case Color\*\*

- Storm grey
- Thunder black

#### Case Material\*\*

- Storm grey models: aluminium (top), PPS (bottom)
- Thunder black models: carbon fiber hybrid (top), PPS (bottom)

#### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

# CONNECTIVITY

#### **Network**

#### Ethernet\*\*

- Gigabit Ethernet, Intel® Ethernet Connection I219-LM (vPro® models), 1x RJ-45, supports Wake-on-LAN
- Gigabit Ethernet, Intel® Ethernet Connection I219-V (non-vPro® models), 1x RJ-45, supports Wake-on-LAN

#### WLAN + Bluetooth®\*\*[1]

- Qualcomm<sup>®</sup> Wi-Fi<sup>®</sup> 6E NFA725A, 802,11ax 2x2 Wi-Fi<sup>®</sup> + Bluetooth<sup>®</sup> 5.3
- Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3

#### WWAN\*\*

- Wireless WAN upgradable to 4G (with antenna ready)
- Quectel EM05-G, 4G LTE CAT4, M.2 card, with embedded eSIM functionality
- · Fibocom L860-GL-16, 4G LTE CAT16, M.2 card, with embedded eSIM functionality
- No support

### SIM Card

No physical SIM card inbox

#### NFC

- · Near Field Communication
- No support

## Notes:

[1] Wi-Fi® 6E full features might be limited by country-level restrictions.

Wi-Fi® 6E is only enabled on Windows® 11 and operates as Wi-Fi® 6 with Windows® 10.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Bluetooth® 5.3 operation requires Windows® 11. For more information please visit <u>General Bluetooth® Support Information on Microsoft®</u>.

### Ports<sup>[1]</sup>

# **Standard Ports**

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 2x Thunderbolt<sup>™</sup> 4 / USB4<sup>®</sup> 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort<sup>™</sup> 1.4)
- 1x HDMI<sup>®</sup> 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)

## **Optional Ports**



\*\*\*

- 1x Smart card reader
- 1x Nano-SIM card slot (WWAN support models)

#### Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

# **Docking**

#### **Docking**

Various docking solutions supported via Thunderbolt™ / USB-C®.

For more compatible docking solutions, please visit Docking for ThinkPad® T14 Gen 4 (Intel®)

# SECURITY & PRIVACY

# Security

### **Security Chip**

Discrete TPM 2.0, TCG certified, FIPS 140-2 certified

### **Physical Locks**

Kensington® Nano Security Slot™, 2.5 x 6 mm

# Smart Card Reader[1]

- Smart card reader, supports ISO 7816 and EMV
- No smart card reader

# Fingerprint Reader[2]

- Touch style fingerprint reader integrated in power button, match-on-chip
- No fingerprint reader

### **BIOS Security**

- NVMe® password
- Power-on password
- Supervisor password
- System management password
- · Certificate-based BIOS athentication
- FIDO (Fast Identity Online) authentication
- Self-healing BIOS

### **Other Security**

- Camera privacy shutter (camera models)
- Ultrasonic Human Presence Detection (IR camera models)
- (Optional) RFID reader<sup>[3]</sup>
- (Optional) IR camera for Windows® Hello (facial recognition)
- Glance by Mirametrix®
- Privacy Guard with Privacy Alert (models with ThinkPad® Privacy Guard display)

#### Notes:

- [1] Smart card reader is mutually exclusive with RFID reader.
- [2] Fingerprint reader is standard on storm grey models and optional on thunder black models.
- [3] RFID reader is mutually exclusive with smart card reader.

# **MANAGEABILITY**

# **System Management**



### System Management\*\*

- Intel® vPro® Enterprise[1]
- Intel® vPro® Essentials<sup>[2]</sup>
- Non-vPro®

#### Notes:

[1], [2] Intel® vPro® offers a superset of DASH's defined capabilities.

# **SERVICE**

# **Warranty**

### Base Warranty\*\*

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty

# **ACCESSORIES**

# **Bundled Accessories**

# **Bundled Accessories**\*\*\*[1]

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo® USB-C® to DisplayPort™ Adapter
- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- Lenovo® USB-C® to VGA Adapter
- None

### Notes:

[1] For more compatible accessory solutions, please visit Accessories for ThinkPad® T14 Gen 4 (Intel®).

# **OPERATING REQUIREMENTS**

# **Operating Environment**

### Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

### **Relative Humidity**

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

#### Notes

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

# **ENVIRONMENTAL**

# **Sustainability**

## Material<sup>[1]</sup>

55% recycled aluminium on storm grey top cover 90% recycled magnesium on keyboard frame 98% PCC recycled plastic used in speaker enclosure



Up to 30% PCC recycled plastic used in the 39.3Wh and 97% in 52.5Wh battery enclosure 90% PCC recycled plastic used in standard 45W and 65W adapters Low-temperature solder Standard packaging: 90% plastic free packaging Bulk packaging: 90% recycled and FSC certified content

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

# **CERTIFICATIONS**

### 

Green Certifications[2]

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered<sup>[3]</sup>
- ErP Lot 6/26
- RoHS compliant
- TCO Certified 9.0

#### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <a href="https://compliance.lenovo.com">https://compliance.lenovo.com</a>.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit <u>epeat.net</u> and <u>energystar.gov</u> for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

# **Other Certifications**

## Mil-Spec Test

MIL-STD-810H military test passed

# **Other Certifications**

(Optional) Eyesafe® Certified 2.0

- Feature with \*\* means that only one option listed under the feature can be configured on selected models.

  Please refer to the model configuration for specific information.
- Feature with \*\*\* means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
  responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
  WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
  OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
  disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
  you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.











